

AVGO POWER-UP HYD Series is formulated performance hydraulic oil to enhance long fluid life, and excellent anti-wear (AW), its apply to wide range of hydraulic system from truck to heavy construction machinery, the selected additives are using well knowd additives technology. In addition the additives is less effect to the rubberseal.



Hydraulic Oil ISO VG		32	46	68	100
Viscosity Grade	ISO	32	46	68	100
Kinematic Viscosity cSt @ 40°C	ASTM D445	32	46	68	100
Kinematic Viscosity cSt @ 100°C	ASTM D445	5.4	6.8	8.8	12
Viscosity Index	ASTM 2770	>95	>95	>95	>95
Flash Point COC °C	ASTM 93	>200	>200	>200	>200
Density @ 15°Ckg/m3	ASTM D4052	880	880	880	890

* High Heat Resistant

* Excellent anti-wear. * Long fluidlife.

Materials Country of Origin Singapore, Japan, Taiwan, Europe, and USA.

Quality Certified to ISO9001:2015





Manufactured / Supplied: **AVGO SOLUTION SDN. BHD.** No.18 & 20, Jalan Permata 8/KS9, Taman Perindustrian Air Hitam, 41200 Klang Darul Ehsan Selangor.

Email: enquiry@avgosolution.com | Tel: +603- 3884 9886 | Fax: +603-3885 7067 | Website: www.avgosolution.com