

AVGO PREMIUM SWY Series is a development of lubricant oil for slide-way application, it has excellent Extreme Pressure additive to provide a high level

of lubricity ,proper stick-slip characteristic, and anti-oxidant for long life.

Heavily-loaded slide ways require increased lubrication characteristics to prevent unwanted metal-to- metal contact. The machine components required formulated oil to drastically reduce friction and increase the performance of slideways, which are also known as linear bearings.

MADE IN MALAYSIA



| Slide Way Oil ISO VG | | 32 | 68 | 220 |
|---------------------------------|------------|------|------|------|
| Viscosity Grade | ISO | 32 | 68 | 220 |
| Kinematic Viscosity cSt @ 40°C | ASTM D445 | 32 | 68 | 220 |
| Kinematic Viscosity cSt @ 100°C | ASTM D445 | 5.5 | 9.2 | 18 |
| Copper Strip Corrosion | ASTM D130C | 1b | 1b | 1b |
| Flash Point COC °C | ASTM 93 | >210 | >230 | >230 |
| Density @ 15°Ckg/m3 | ASTM D4052 | 880 | 890 | 890 |
| Viscosity Index | ASTM 2270 | >95 | >95 | >98 |

Materials Country of Origin Singapore, Japan, Taiwan, Europe, and USA.

Quality Certified to ISO9001:2015





Manufactured / Supplied:

AVGO SOLUTION SDN. BHD. No.18 & 20, Jalan Permata 8/KS9, Taman Perindustrian Air Hitam, 41200 Klang Darul Ehsan Selangor.

Email: enquiry@avgosolution.com | Tel: +603- 3884 9886 | Fax: +603-3885 7067 | Website: www.avgosolution.com