

Description

Performance circulating oil:

AVGO OIL PERFOLINE is a series of Zinc Free and Ash Free circulating oil designed for high performance dual lubricating application in Hydraulic, and Slide way system.

AVGO OIL PERFOLINE is formulated with highly refined group II paraffinic base oil with high performance additives which its can provide superior thermal stability, de-emulsification, anti rust, anti corrosion, anti foam, anti wear and anti oxidation.

AVGO OIL PERFOLINE can be applied from light to heavy duty machinery with high load pressure and high temperature condition, it has a unique combination of additives to be able applied in wide range of machines which required high performance circulating oils with high viscosity index.

PERFOLINE SERIES		HP1	HP 2	HP 4	HP 6	HP 8	HP10	HP12
Viscosity Grade	ISO	22	32	46	68	100	150	220
Kinematic Viscosity cSt @ 40°C	ASTM D445	21.8	31.5	45.4	68.4	100	150	225
Kinematic Viscosity cSt @ 100°C	ASTM D445	4.4	5.44	7.2	10.3	13.8	19	15
Viscosity Index	ASTM 2270	110	112	131	137	139	143	143
Flash Point COC °C	ASTM 93	220	230	240	246	264	279	289
Density @ 15°C kg/m³	ASTM D4052	0.86	0.86	0.87	0.87	0.88	0.89	0.895
Copper Corrosion. (100°C @ 3 hours)	ASTM D130	la	la	la	۱a	la	la	1a
Description	* Excellent anti-wear. * Thermal stability * Long fluid life.							

* Excellent anti-wear. * Thermal stability * Long fluid life.

Country origin of materials:

Certified to ISO9001:2015

RoHS Compliant

Quality

Singapore, Japan, Taiwan, Europe, USA



Manufactured & Supplied by:

AVGO SOLUTION SDN BHD No.18 & 20, Jalan Permata 8/KS9, Taman Perindustrian Air Hitam, 41200 Klang Selangor.

For further information. please contact: Ema Tel: +603-38849886 Fax : +603- 3885 7067 Website



